

SPEC-D *Tuning*

2006-2008 HONDA CIVIC COUPE PROJECTOR HEADLIGHTS INSTALLATION INSTRUCTIONS



- *If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise.
- *Please wear protection before you work on your vehicle.
- *An assistant is helpful when removing the front bumper.
- *Please be careful while working with the bumper or body part to avoid scratching.
- *Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED

Name of the Tools, from left to right:

Phillips Screwdriver
Trim Pad Remover
1/2" Drive Ratchet
1/2" Drive Extensions (8 to 10 inches)
5 mm Hex Sockets

10mm Socket

IF YOUR HEADLIGHT IS HALO TYPE, YOU ALSO NEED.

Wire Stripper
Wire Crimper
4 Blue Quick Splice Wire Connectors
4 Blue Male Quick Wire Connectors
4 Blue Female Quick Wire Connectors

2 Red Wires (8 inch)

2 Black Wires (8 inch)

Product Part Numbers:

2LHP-CV064-TM
2LHP-CV064B-TM
2LHP-CV064JM-TM
2LHP-CV064JMB-TM





*If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise.

*Please wear protection before you work on your vehicle.

*An assistant is helpful when removing the front bumper.

*Please be careful while working with the bumper or body part to avoid scratching.

*Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.



1. Open the hood



2. And then remove the four clips from the top of the grill



3. Remove the clips



4. Remove the cover



5. There are two bolts needed to be removed



6. Remove two 5mm hex bolts



7. Remove fourteen clips under the bumper



8. Remove one bolt at side of the bumper (Both side)



9. Pull out the bumper



10. Remove the bumper slightly



11. Remove one 10mm headlight bolt under the headlight



12. Remove one 10mm headlight bolt at side of the headlight



13. Remove the bracket under the headlight



14. Remove two 10mm headlight bolts on the top of the headlight



15. Remove two 10mm headlight bolts on the top of the headlight



16. Disconnect all connectors from the headlight



17. Remove the headlight



18. Install all headlight connectors
please see the "Halo and L.E.D. installation instructions"
If your headlights don't have HALO or L.E.D. You can skip the installation instructions.



19. Install the headlight



20. Install the bracket under the headlight



21. Install all headlight bolts



22. Install the front bumper



23. Install two 5mm hex bolts



24. Install one bolt at side of the bumper (Both side)



25. Install fourteen clips under the bumper



26. please repeat the picture order from 1 to 26 for the opposite side



27. The installation now is complete

