

SPEC-D *Tuning*

2009-UP HONDA FIT L.E.D. TAIL LIGHTS INSTALLATION INSTRUCTIONS



- *If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise.
- *Please wear protection before you work on your vehicle.
- *An assistant is helpful when removing the front bumper.
- *Please be careful while working with the bumper or body part to avoid scratching.
- *Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.

TOOLS AND SUPPLIES REQUIRED



Product Part Numbers:

LT-FIT09CLED-TM
LT-FIT09GLED-TM



2009-UP HONDA FIT L.E.D. TAIL LIGHTS INSTALLATION INSTRUCTIONS



*If you experience any difficulties that the instruction did not cover, Please seek local auto shop for advise.

*Please wear protection before you work on your vehicle.

*An assistant is helpful when removing the front bumper.

*Please be careful while working with the bumper or body part to avoid scratching.

*Do not make direct contact with the halogen bulb or the wire assembly until the unit has cooled down after use.



1. First open the trunk



2. Use a flat-tip screwdriver to loosen the clips behind the cover



3. Remove the cover



4. After you pull out the cover, you will see all the wires, connector harnesses, and three screws



5. Pull out all the wires and connectors from the vehicle



6. Remove the three screws



7. Gently pull out the OEM tail light



8. After removing the OEM tail light, it should look the same as the picture shown above



9. Remove all the sockets from the OEM tail light



10. Plug all the sockets into the new L.E.D. tail light



11. Remove the light bulb from the OEM socket

Please see the "L.E.D. Tail Light Installation Instructions" if your tail lights don't have L.E.D., you can skip the installation instructions.



12. Plug the male harness from the L.E.D. tail light to the new L.E.D. sockets by gently pushing them in for a snug fit



13. Replace the sockets back into the L.E.D. tail light



14. Gently place the L.E.D. tail light back into vehicle



15. install the three screws to fasten the tail light



16. Connect all the connectors



17. Put the cover back into the place
(Please repeat the picture order from 1 to 12 for the opposite side)



18. The installation is now complete

SPEC TUNING